

# MATERIAL SAFETY DATA SHEET

HMIS CODES: 

H	F	R	P
0	2	0	A

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor  
Occupational Safety and Health Administrator  
(Non-Mandatory Form)  
Form Approved OMB No. 1218-0072

IDENTITY (AS USED ON LABEL AND LIST):  
**BLUE MONSTER™ THREAD SEAL COMPOUND**

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

## Section I

Manufacturer's Name:  
THE MILL-ROSE COMPANY

Emergency Telephone Number:  
(800) 321-3598

Address (Number, Street, City, State, and ZIP Code):  
7310 CORPORATE BLVD.

Telephone Number for Information:  
(800) 321-3598

Date Prepared: January 1, 2008

MENTOR, OHIO 44060

Signature of Preparer (optional):

## Section II - Hazardous Ingredients/Identity Information

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY: COMMON NAME(S))	OSHA PEL	ACGIH TLV	OTHER LIMITS Recommended	% (optional)
ISOPROPYL ALCOHOL [CAS#67-63-0]	400	400	N/A	5 - 10
ETHYLENE GLYCOL [CAS#111-76-2]	50	25	N/A	13 - 18

## Section III - Physical/Chemical Characteristics

Boiling Point:	180°F	Specific Gravity (H2O = 1):	1.41
Vapor Pressure (mm Hg):	.88	Melting Point:	N/A
Vapor Density (AIR = 1):	> 1	Evaporation Rate (Butyl Acetate = 1):	.6
Solubility in Water:	SLIGHT	VOC Content:	310 g/l

Appearance and Odor: BLUE PASTE - MILD ODOR

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): 82°F (28°C) ASTM METHOD D93-80	Flammable Limits: 921°F (494°C) IGNITION TEMPERATURE	LEL: 0.9%	UEL: 6.0%
---	--	--------------	--------------

Extinguishing Media: CARBON DIOXIDE OR DRY CHEMICAL OR WATER.

Special Fire Fighting Procedures: NONE

Unusual Fire and Explosion Hazards: CONTACT WITH STRONG OXIDIZERS MAY CAUSE FIRES OR EXPLOSIONS. CARBON MONOXIDE MAY BE RELEASED.

<b>Section V - Reactivity Data</b>		<b>BLUE MONSTER™ THREAD SEAL COMPOUND</b>	
Stability:	Unstable:		Conditions to Avoid: N/A
	Stable:	X	
Incompatibility (Materials to Avoid): LIQUID OXYGEN SYSTEMS, LIQUID SODIUM, GASEOUS FLUORINE, STRONG OXIDIZERS.			
Hazardous Decomposition or Byproducts:			
Hazardous Polymerization:	May Occur:		Conditions to Avoid: N/A
	Will Not Occur:	X	
<b>Section VI - Health Hazard Data</b>			
Route(s) of Entry:	Inhalation? YES	Skin? YES	Ingestion? YES
Health Hazards (Acute and Chronic): N/A			
Carcinogenicity:	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO
Signs and Symptoms of Exposure: INHALATION: POSSIBLE DIZZINESS IF USED IN CONFINED AREA. SKIN: MAY CAUSE MILD IRRITATION TO SENSITIVE SKIN.			
Medical Conditions Generally Aggravated by Exposure: NONE KNOWN			
Emergency and First Aid Procedures: EYE CONTACT: FLUSH EYES WITH WATER. SKIN CONTACT: WASH SKIN WITH SOAP AND WATER. WASH CLOTHING BEFORE REUSE. INHALATION: MOVE TO WELL VENTILATED AREA. INGESTION: CALL PHYSICIAN.			
<b>Section VII - Precautions for Safe Handling and Use</b>			
Steps to Be Taken in Case Material is Released or Spilled: NORMAL GOOD HOUSEKEEPING PROCEDURES.			
Waste Disposal Method: DISPOSE OF ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.			
Precautions to Be Taken in Handling and Storing: STORE AWAY FROM HEAT OR OPEN FLAME. CLOSE CONTAINER AFTER USE.			
Other Precautions: WEAR PROTECTIVE GLOVES TO PREVENT POSSIBLE SKIN ABSORPTION AND DERMATITIS. KEEP OUT OF REACH OF CHILDREN.			
<b>Section VIII - Control Measures</b>			
Respiratory Protection (Specify Type): AVOID BREATHING OF FUMES. IF USED IN A CONFINED AREA, A RESPIRATOR MAY BE NECESSARY.			
Ventilation:	Local Exhaust: NORMAL VENTILATION IS ADEQUATE.		Special: N/A
	Mechanical (General): N/A.		Other: N/A
Protective Gloves: MAY BE NECESSARY FOR SENSITIVE SKIN.		Eye Protection: KEEP OUT OF EYES. WEAR PROTECTIVE GOGGLES WHERE NECESSARY.	
Other Protective Clothing or Equipment: N/A			
Work/Hygienic Practices: WASH UP WITH SOAP AND WATER AFTER USE.			